



Interactive QLED Touch Panel


Available in sizes 65" 4K | 75" 4K | 86" 4K

Power Meets Precision, Engineered for Excellence

Parrot's Interactive Flat Panels are built to empower collaboration, education & innovation. Assembled in South Africa and backed by lifetime remote support, these panels combine world-class technology with local reliability.

Whether you're teaching, presenting, or managing,
Parrot Interactive Flat Panels deliver performance you can trust.


Connect. Collaborate. Create



4K Resolution




QLED




8 Cores



Anti Glare




8GB RAM



128GB Storage



Wi-Fi 6



Multi Touch

Interactive Innovation for Modern Environments

Powered by
android 



Public Sector



Education



Corporate Spaces



Google EDLA certification is designed for interactive displays and smart boards, ensuring they come with built-in Google Mobile Services



5 Year Warranty
This Limited Warranty is conditioned upon proper use and installation of the product.
Refer to Warranty T's & C's



EShare is a full-featured multi-screen interactive software designed for casting, wireless display and remote control between mobile devices and large displays.



CDM system is a centralized equipment control and management system, which aims to facilitate customers to remotely manage with screenshot support.



Collaborate, create, and share ideas instantly with the built-in digital whiteboard.

Technical Features



Ultra Performance

- RK3588 Octa-core CPU 8-Cores, 8GB RAM, 128GB Storage Android 13 with EDLA Certification (Full Google Play Access)



Incredible Display

- True 4K QLED
- 93% NTSC Colour Gamut • Anti-glare glass
- Optical bonding • 1.07 billion colours



Touch & Writing

- IR Touch
- 20 points (Android), • 50 points (Windows)
- Pen & Finger input • <3ms response time



Wireless Casting Suite

- Cast from any device (Airplay, Miracast, DLNA, Chromecast)
- Touchback control • Moderator mode
- Webcast (no app needed)



Centralized Device Management

- Remote control, • Updates, • App management,
- Alarms, and scheduling • Real-time monitoring
- Batch workflows • Sub-account control



Built-in Interactive Tools

- Floating menu • Eye protection mode
- Whiteboard with annotations • AI tools
- Power management with scheduling and energy-saving modes

Certifications & Support

- NRCS & ICASA Certified
- Free Online Training via Parrot Academy
- Lifetime Remote Support
- 5-Year Factory Warranty
- Refer to Warranty T's & C's

Accessories included:

- Wall Bracket
- HDMI Cable
- USB Touch cable
- Power Cable
- 2 x Stylus Pens

Ideal for:

Education

- Smart classrooms • Student casting
- Built-in teaching tools • Remote IT management

Corporate

- Wireless boardroom presentations
- Moderator control • Secure device management • App integration

Public Sector

- Centralized control • Scheduled content & power • Multi-user access
- Compliance-ready





Technical Specifications

65" IP0065B | 75" IP0075B | 86" IP0086B

Display

Display area	65" - 1428 x 803 mm 75" - 1650 x 928mm 86" - 1895 x 1066mm
Back light	D-LED
QLED - colours	93%NTSC
Display colours	1.07Billion
Bonding	Optical Bonding
OD	35
Display ratio	16:9
Resolution	3840 x 2160 (4K UHD)
Glass	4mm Anti-glare
Low blue light	Support
Center brightness	350 cd/m² (typ.)
Contrast ratio	1200 : 1 / 4000 : 1
Response time	8ms (typ.)
Viewing angle	H = 178, V = 178 typ.
Display life time	≥ 50000 hours

Touch Technology

Touch solution	IR
Surface treatment	Anti glare
Transparency	88 % ± 3
Fod degree	4 - 8%
Hardness	> 7H
Touch accuracy	Φ 1mm
Response time	≤ 3ms
Touch point	Android 20 & Windows 50
System support	Windows, Mac, Android, Linux, Chrome
Touch screen writing tools	Stylus Pen & Finger

Storage Environment & Dimensions

Storage temperature	-10 ~ 55°C -20 ~ 90%RH
Operating temperature	0 ~ 55°C -20 ~ 80%RH
Installation method	Wall hanging / Stand
Overall dimensions	65" - 1487.3 x 903.9 x 116mm 75" - 1712.9 x 1014 x 115.6mm 86" - 1955 x 1182 x 115.6mm
Package size	65" - 1580 x 1000 x 200mm 75" - 1785 x 1125 x 200mm 86" - 2044 x 1280 x 200mm
Net weight	65" 35 ± 1KG 75" 46.5 ± 1KG 86" 59.5 ± 1KG
Gross weight	65" 44 ± 1KG 75" 57 ± 1KG 86" 71.5 ± 1KG

Smart System & Performance

CHIP	RK3588
CPU / GPU	4 x A76(Max:2.4GHz) Quad - 4 x A55 (Max:1.8GHz)
RAM	8G
Flash memory	128GB
Android version	Android 13
EDLA	Yes

Rear I/O

RS232	DB9 x 1
COAX / SPDIF	COAX x 1
RJ 45	1000M x 2
LINE OUT	3.5mm x 1
USB 3.0	x 3
VGA	x 1
AUDIO IN	3.5mm x 1
TOUCH USB	3.0 x 3
TYPE-C OUT	DP 1.2 x 1
TYPE-C IN	DP 1.2 x 1
HDMI IN	2.0 x 3
HDMI OUT	2.0 x 1
DP IN	1.2 x 1
MIC IN	3.5mm x 1
TF CARD	x 1
OPS SLOT	x 1 Supports standard OPS modules for Windows PC integration

Connectivity

Wi-Fi	Wi-Fi 6 802.11a/b/g/n/ac/ax
Bluetooth	5.2
Speaker	15w x 2
Wireless casting	Yes
Hotspot	Yes

Electrical Parameter

Working Voltage	AC100 - 240V
Power Consumption (full load)	65" ≤ 250W 75" ≤ 350W 86" ≤ 450W
Power Consumption (standby load)	< 0.5W