



# Wireless PTZ Voice Tracking Webcam



USB Receiver



Voice tracking



20m Transmission



10x Optical zoom




4 Mic array



1080p 30fps





## VC0005 Technical features:



### Features

- Camera automatically rotates & tracks the voice
- 2.4G wireless connection, 300ms latency time, Cable free
- 4 Digital Microphone Array & 10m voice pickup
- 2.1 million pixels, 1/2.9" HD color CMOS
- 1080P/30fps, 720@30fps
- Adopt AGC technology
- 10x Optical zoom
- IR Remote Control

Camera, Lens parameters	Image Sensor	1/2.9 inch CMOS Sensor
	Min Lux	0.1Lux(F1.2)
	Effective Pixel	2.1 MP
	Focus Mode	10x Optical zoom
	Shutter Speed	1 to 1/10000s
	Horizontal Field of View	54.8°(W)~5.8°(T)
	Frame Rate	1920×1080,1280×720, 640×480
Microphone parameters	Aperture Mode	Manual
	Backlight Compensation	Support
	Wide Dynamic	Support
	Picture Adjustment	Brightness、 Chroma、 Saturation、 Contrast、 Acut
	MIC Array Quantity	4
	MIC Array Form	Linear
	Microphone Spacing	35mm
2.4G wireless parameters	Sampling Rate	16KHz/48KHz
	Sensitivity	-29dBfs
	Voice pickup range	0-10meters
	Horizontal Voice Pick up Angle	Horizontal 180°
	SNR	65.5dB
	Communication Mode	full duplex
	Wireless range	20m indoor and 50m in open air
Interface Parameter	2.4G working frequency range	2.400GHz~2.4835GHz
	Wireless power output	≤100mW
	Video Compressed Format	MJPEG
	Control Interface	RS-232, UVC
	Control Agreement	VISCA/PELCO-D/PELCO-P
PTZ Parameter	Communicate Baud Rate	2400/4800/9600/115200
	Power Interface	DC-038 power socket (DC12V)
	Pan Rotation	-170°~ +173°
	Tilt Rotation	-30°~ +90°
	Horizontal Rotate Speed	0.1~100°/second
Other Parameters	Vertical Rotate Speed	0.1~80°/second
	Power Adapter	Input AC100V~AC240V Output DC12V/2A
	Decoder	Built in
	Input voltage	DV12V
	Power Consumption	12W(MAX)
	Storage Temperature and Humidity	-10°C ~ +60°C / 20% ~ 95%
	Working temperature and Humidity	-10°C ~ +50°C / 20% ~ 80%
	Operating Environment	Indoor
	Baud Rate	2400/4800/9600/115200
	Protocol	VISCA / PELCO-D / PELCO-P
	Address Setting	Max 1~255, 10 via remote
Dimensions	160.7*115.1*131.4mm	
Weight	600g	